

ADS-110DL-19-1 240072E

DC24V 3A Power Adapter



Features

- Easy installation;
- 90~264Vac wide input voltage range, meet the requirements in different parts for electric network fluctuation;
- High quality and reliability: pass 3 months high temperature aging test;
- ± 2 KV outdoor lightning protection grade.

Technical Specification	
Model	ADS-110DL-19-1 240072E
Electrical Specification	
Input Voltage Range	90~264Vac
Output Plug	18AWG 1185 1.2M black magnet
Efficiency	62.5% (V)
Output Voltage	24Vdc (+5%, -5%)
Output Current	3A
Max. Output Power	72W
No Load Power Consumption	<0.21W
Protection/Environmental	
Protection	Surge protection, over temperature protection, short circuit protection, over current, voltage load protection
	ESD: IEC61000-4-2 ±4kV Contact ±8kV Air
Working Temperature	+0 ℃ ~ +45 ℃ (+32 ℉ ~ +113 ℉)
Working Humidity	10% ~ 90% RH
Physical Properties	
Weight	0.28kg (0.62lb)
Dimension(LxWxH)	156mm(L)* 58mm(W)*33.5mm(H) (6.14"x2.28"x1.32")
Installation	Desk-mount
Color	Black
DC Plug	Straight Φ6.5*Φ1.35*10mm(Φ0.26"xΦ0.05"x0.39")
Safety Standards	
Certification	CCC/CE/UL/EAC/RCM

Optional Power Cord

European 2-pin	Line long: (1500±50)mm Weight: 170g
American 3-pin	Line long: (1500±50)mm Weight: 140g
British 3-pin	Line long: (1500±50)mm Weight: 190g
Brazilian(new) 3-pin	Line long: 1500mm Weight: 130g
(little)South African 3-pin	Line long: (1500±50)mm Weight: 180g
South African 2-pin	Line long: (1500±50)mm Weight: 170g

Dimensions (mm/inch)

