

DSC

From Tyco Security Products

with
PowerG
Technology

2-Way DSC PowerG Wireless arming station **WS9LCDWFx**



Features that Making a difference:

- 2 x 16 Full Message Display
- Automatic clock programming
- Multi doorbell
- Blue screen
- White keyboard backlight
- Displays the temperature
- Multiple language support: English, French, Spanish
- 5 preset function keys
- Tamper switch
- Arm / Disarm
- System status
- Zone status
- Bypass zones

The WS9LCDWFx wireless arming station is part from the iotega security program & lifestyle solution. iotega is a platform for Home automation and smart security all in one, highly secure and flexible for residential properties and small commercial. Elegant, stylish and compact,

can be placed in any room, combining perfectly with any decor.

The power of PowerG:

The power behind WS9LCDWFx lies in several innovative technologies, including the revolutionary PowerG, which, combined, provide a solid and rich platform in functions designed to reduce operating costs for distributors and provide maximum reliability for end users.

- Multichannel, frequency hopping Spread Spectrum Technology allows the system to hop between wireless frequency channels to ensure the Smooth transmission of secure communications between devices and the control panel.
- Adaptive transmission power reducing battery replacement costs incurred.

- High transmission ranges allow the devices to communicate reliably up to 2 km / 1.24 miles in line of sight, reducing the cost of installing additional repeaters to give service to larger facilities.
- 1 TDMA synchronized communication technology prevents messages from colliding by splitting the channels into several time intervals, allowing for greater amount of data transmission and ensures that devices can communicate constantly when necessary.
- 128-bit AES encryption offers a level exceptionally high protection against digital analysis and attack tools.

Specs:

Protection class of the plastic housing..... IP30

Dimensions..... 168 mm x 122 mm x 25 mm
(6 39/64" x 4 51/64" x 63/64")

Battery 4 AA, 1.5V Power Consumption

Board current 30mA (standby) 105mA (max.) Environment

operating -10°C to 55°C (14°F to 131°F) Relative humidity

..... 5 to 93%

Approvals:

FCC/IC, UL/ULC, CE, SIA CP-01, CSFM

Please refer to www.dsc.com for the most up-to-date approval lists.

Compatibility:

The WS9LCDWFx is compatible with the iotega system

Ordering information:

WS9LCDWF9 915MHZ Wireless PowerG Arming Station WS9LCDWF8

..... 868MHZ Wireless PowerG Arming Station

Optional desktop stand with transformer	
US	LCDWFDMMK-US
Canada	LCDWFDMMK-C
Eastern Europe	LCDWFDMMK-EU
Eastern Europe	LCDWFDMMK-UK