

Switches and Buttons

Tamper Switches

SS-072Q For normally closed sabotage circuits

SS-073Q For normally open sabotage circuits

- For drawers and alarm
- boxes Silver plated contacts
- Rated 0.5A@24V DC



Latching Switch

SS-076Q/SW snow White

- SPST toggle switch rated 3A@125V DC
- Attractive plastic case with two screw holes
- 6" (15 cm) leads prewired



Push Buttons

Momentary

SS-032Q/RD Red button NA

SS-033Q/BK NC black button

- Fits a hole of 1/2" (13 mm)
- Classified 1A@12V DC



SS-032Q/RD



SS-033Q/BK

Sheet Connection Block **SS-202Q**

- Double lock
- Self-adhesive mounting
- Ramping metal plate reduces sheet breaks



Hold Buttons

SS-077Q NC Push-to-open operation

SS-078Q NA Push-to-close operation

- Latching push button, flag shows when pressed
- High impact ABS case, stainless steel cover.
- SPST switch rated 1A@12V DC
- Two reset keys included



Shock Vibration Sensors

SS-040Q/BR NC, brown

SS-040Q/W NC, white

- Detects impacts on window glass, walls or ceilings Gold plated contacts for longer life and reliability
- Built-in tamper switch for complete safety
- Adjustable from 1~50g 1@50V DC
- Size: 2 3/8" X 1 3/16" X 5/8"



SS-040Q/BR



SS-040Q/W

Push Buttons

Momentary

SS-074/BG NA Push-to-close operation

- Dual button operation virtually eliminates accidental firing
- Rugged metal housing, silver plated SPST contacts, pre-wired for quick installation
- Rated 1A@25V DC



DRY-LARM®USA, Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone:(949) 261-2999 | (800) 662-0800Fax:(949) 261-7326

Website:www.seco-larm.comE-mail:sales@seco-larm.com



Copyright © 2019 SECO-LARM USA, Inc. All rights reserved.
All trademarks are the property of SECO-LARM USA, Inc. or their respective owners.
SECO-LARM's policy is one of continuous development and improvement. For this reason, SECO-LARM reserves the right to change specifications and prices without notice. SECO-LARM is also not responsible for printing errors.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA® SLI®

PI_SS-xxxx_190523_ML.docx

Switches and Buttons

Tamper Switches

SS-072Q For normally closed tamper circuits

SS-073Q For normally open tamper circuits

- For drawers and alarm
- Silver-plated contacts
- Rated 0.5A@24VDC



Toggle Switch

SS-076Q/SW Snow-white

- SPST Toggle switch rated 3A@125VDC
- Attractive plastic case with two screw holes
- Pre-wired 6" (15cm) leads



Momentary Push Buttons

SS-032Q/RD Red NO button

SS-033Q/BK Black NC button

- Fits 1/2" (13mm) hole
- Rated 1A@12VDC



SS-032Q/RD



SS-033Q/BK

Foil Connection Block

SS-202Q

- Double-blocked
- Self-adhesive mounting
- Ramped metal plate reduces foil breaks



Hold-up Buttons

SS-077Q NC Push-to-open operation

SS-078Q NO Push-to-close operation

- Latching push button, flag shows when pressed
- High-impact ABS case, stainless steel cover
- SPST Switch rated 1A@12VDC
- Two reset keys included



Vibration Shock Sensors

SS-040Q/BR NC, brown

SS-040Q/W NC, white

- Detects shock to window glass, walls, or ceiling
- Gold-plated contacts for longer life and reliability
- Built-in tamper switch for complete security
- Adjustable from 1~50 g
- 1@50VDC
- Size: 2 3/8" x 1 3/16" x 5/8"



SS-040Q/BR



SS-040Q/W

Momentary Push Button

SS-074/BG NO Push-to-close operation

- Double-button operation virtually eliminates accidental triggering
- Sturdy, metal case, silver-plated SPST contacts, pre-wired for quick installation
- Rated 1A@25VDC

