

HDMI-30

This HDMI cable is designed for stable and high-quality audio and video transmission. It features strong shielding and durable materials to ensure reliable performance for home entertainment, office setups, and other multimedia applications. Ideal for connecting TVs, monitors, and digital devices.



Technical Specifications

Item	Description
Product Spec	(30AWG*1P+1C+AL)*5P + 30AWG*4C +FDA
Length	3.0 meter
OD	8.0mm (Black Matt)
5 Pair Conductor	1/0.254±0.008 Tinned Copper (10 wires)
Insulation	HD/PE TR144 (White/Blue)
Version	2.0
Resolution	4K Resolution
Twisting	S/P:16±10
Drain Wire	1/0.20±0.008 Tinned Copper (5 pairs)
Shielding	6MM Al/Mylar - Red mark
30AWG*4C Conductor	1/0.20±0.008 Tinned Copper (4 wires)
Insulation	HDPE TR144 (White, Black, Purple, Red)
Twisting	All cores twisted S/P:85±10
Filling	Filler 6000D
Overall Shield	20MM Al Foil +Wrap
Overall Drain	1/0.20±0.008 Tinned Copper (1 wire)
Jacket	60P BK01-065-00 Black
Outer Diameter	8.0±0.2mm
Extrusion	Overall Extruded