



DataSheet

VIDEO & AUDIO

- **IP Video Input: 16 channels**
- **Incoming Bandwidth: 80 Mbps**
- **Outgoing Bandwidth: 60 Mbps**
- **HDMI Output Resolution: 1 channel — 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz**
- **VGA Output Resolution: 1 channel — 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1280x720/60Hz**
- **Video Output Mode: Simultaneous HDMI/VGA output**
- **Multi-View Display: 1/4/6/8/9/16**

DECODING

- **Audio Compression: G.711A / G.711U / G.726**
- **Video Compression: H.265+ / H.265 / H.264+ / H.264**
- **Recording Resolution: 8MP / 5MP / 4MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF**
- **Synchronous Playback: 16 channels**
- **Capabilities:**
 - **25 fps: 2-ch @ 8MP, 4-ch @ 4MP, 8-ch @ 2MP**
 - **30 fps: 4-ch @ 3MP, 2-ch @ 5MP**

RECORDING MANAGEMENT

- **Recording Modes: Manual, scheduled, motion detection**
- **Playback Modes: Instant playback, regular playback, tag playback, event playback**

- **Backup Mode:** Normal backup, video clip backup
- **Playback Functions:** Play, Pause, Stop, Fast forward, Rewind, Frame-by-frame, Full screen, Video clip, Export clip, Digital zoom, Lock recording, Enable/Disable audio

NETWORK

- **Protocols:** UPnP, NTP
- **Mobile Access:** Android, iOS
- **Supported Browsers:** Chrome (57+), Firefox (52+), Edge (91+)
- **Interoperability:** ONVIF, CGI

EXTERNAL INTERFACE

- **Network:** 1 × 10/100/1000 Mbps adaptive RJ-45 Ethernet port
- **USB:** 1 × front USB 2.0, 1 × rear USB 2.0
- **Audio:** 1 input, 1 output
- **Alarm I/O:** N/A
- **Serial Interface:** N/A
- **Power:** 1 × DC connector
- **Reset Button:** 1
- **Speaker:** N/A
- **eSATA:** 1
- **HDMI:** 1
- **VGA:** 1

HARD DISK

- **SATA: 2 interfaces**
- **Capacity: Up to 10 TB per hard drive**

PoE

- **Standard: Complies with 802.3at/af**
- **Ports: 1–16 × 10/100 Mbps adaptive RJ-45 Ethernet ports**
- **Power Budget: 90 W total, max. 30 W per port**

ALARMS

- **General: Motion detection, video tampering, line crossing, intrusion, region entrance, region exit, object removal/abandonment, vehicle detection, human detection, smart frame**
- **Exception: Video loss, IP conflict, disconnection, disk error, login exception, fan error**
- **Alarm Linkage: Recording, white light alarm, buzzer, log, audible alarm**

GENERAL

- **Storage Temperature: -40 to 70 °C**
- **Storage Humidity: 10%–90% RH (non-condensing)**
- **Package Contents: VIGI Network Video Recorder, Power adapter, Power cables, HDD power cables, HDD data cables, Mounting accessories, Mouse, Quick installation guide**
- **Operating Temperature:**
 - **NVR: -10 to 55 °C**
 - **Power adapter: 0 to 40 °C**
- **Operating Humidity: 10%–90% RH (non-condensing)**

- **Dimensions (W × D × H): 330 × 285 × 45 mm**
- **Net Weight: 1.9 kg**
- **Gross Weight: 3.2 kg**
- **Power Supply: 53.5 V DC / 2.43 A**
- **Max. Power Consumption: 6.2 W (without HDD), 40 W (with HDD)**
- **Certifications: CE, EAC, UKCA, RCM, Triman, BSMI, VCCI, FCC, IC, HDMI**