

DataSheet

WIRELESS

- Standards and Protocols: Wi-Fi 5
 - IEEE 802.11ac/n/a 5 GHz
 - IEEE 802.11n/b/g 2.4 GHz
- WiFi Speeds (AC1900):
 - 5 GHz: 1300 Mbps (802.11ac)
 - 2.4 GHz: 600 Mbps (802.11n)
- WiFi Range: Homes with 3 to 5 bedrooms (3-pack)
 - TP-Link mesh technology
 - Optional Ethernet backhaul links Deco units for seamless coverage
- Antennas: 3 × internal
 - Multiple antennas enhance signal in more directions and larger areas
- Beamforming: Focuses signal toward clients to extend WiFi range
- WiFi Capacity: Medium, Dual-band
 - Distributes devices across bands for optimal performance
- MU-MIMO: Communicates simultaneously with multiple clients

• Working Modes: Router mode, Access Point mode

SECURITY

- Network Security: SPI firewall, Access control
- Guest Network:
 - 1 × 5 GHz guest network
 - 1 × 2.4 GHz guest network
- WiFi Encryption: WPA-Personal, WPA2-Personal

HARDWARE

- Ethernet Ports: 3 Gigabit ports per Deco unit (auto WAN/LAN detection)
- Buttons: Reset button

SOFTWARE

- Protocols: IPv4, IPv6
- Parental Controls: URL filtering, Time control
- WAN Type: Dynamic IP, Static IP, PPPoE, PPTP, L2TP
- Quality of Service: Device-based QoS

- Cloud Service: OTA firmware updates, TP-Link ID, DDNS
- NAT Forwarding: Port forwarding, UPnP
- IPTV: IGMP Proxy, IGMP Snooping, Bridge, VLAN tagging
- DHCP: Reservation, Client list, Server
- DDNS: TP-Link
- Management Features: Deco App

OTHER

- Network Services Enabled by Default:
 - Web Server: Manage and configure device through web (HTTP/HTTPS) • Port: 80/443 • Protocol: TCP
 - DNS: Port 53 Protocol: TCP & UDP
 - DHCP Server: IP address assignment Port 67 Protocol: UDP
 - App Management: Ports 22, 20001, 30001 (TCP), Port 20002 (UDP)

TEST DATA

- WiFi Transmission Power:
 - CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz)

FCC: <30 dBm (2.4 GHz), <30 dBm (5 GHz)

PHYSICAL

- Dimensions (W×D×H): 6.4 × 3.6 × 3.6 in (162.3 × 90.7 × 90.7 mm)
- Package Content:
 - Deco S7 (3-pack): 3 Deco S7 units, 1 Ethernet cable, 3 power adapters, Quick installation guide
 - Deco S7 (2-pack): 2 Deco S7 units, 1 Ethernet cable, 2 power adapters, Quick installation guide
 - Deco S7 (1-pack): 1 Deco S7 unit, 1 Ethernet cable, 1 power adapter, Quick installation guide

OTHERS

- Certification: CE, FCC, RoHS, NCC, BSMI, JRF, JPA, VCCI
- System Requirements: Android 5.0 or later, iOS 9.0 or later
- Environment:
 - Operating Temperature: $0 \,^{\circ}\text{C} \sim 40 \,^{\circ}\text{C}$ (32 °F ~ 104 °F)
 - Storage Temperature: -40 °C ~ 60 °C (-40 °F ~ 140 °F)
 - Operating Humidity: 10% ~ 90% non-condensing
 - Storage Humidity: 5% ~ 90% non-condensing