



SL01-A630N

Smart Keyless Entry lever Lock



Mobile
App



Fingerprint



Passcode



Card



Key



Compatible With

NGTeco Home App



Introduction

The **SL01-A630N** is a lever lock designed for use in residential settings. The straightforward design offers high security and reliability, making it an ideal choice for users who priorities simplicity and smart technology. The Bluetooth 5.0 technology enables swift connection with mobile applications. The **NGTeco home** App offers access to user management, log history checking, and the option to share temporary visitor passwords. With an additional Bluetooth gateway, users can benefit from remote control functionality.

The **SL01-A630N** is well-suited for residential and office doors, with straightforward installation and operation suitable for users of all technical levels.

Features



Remote Control

With Bluetooth gateway, user can unlock and manage the lock from anywhere, anytime



Unlock Records Checking

View the logs of who has opened the lock



Temporary Password Sharing

Sharing access with temporary passwords for visitors



Fingerprint-Type Handle Design

Enjoy one-step fingerprint recognition and unlocking experience



Low Battery Alert

Get a notification when the battery is low



Smart Warning

Error-Detection alert for any abnormal behavior



USB Type-C Interface

Equipped with a commonly used Type-C emergency power interface



Mechanical Key Override


Get a physical key for emergency door opening

Specifications


Material	Housing Material	Aluminium Alloy
	Color Options	Black
Mortise Lock	Type	American Single Latch
	Backset	Adjustable 60 or 70 mm
Technical	Unlocking Methods	Fingerprint, Card, Passcode, NGTeco Home APP, Mechanical Key
	Capacity	100 (Fingerprint + Passcode + Card)
	Fingerprint Sensor	Capacitive
	Card Reader	IC Card @13.56 MHz NFC Supported
	Wireless Communication	BLE 5.0
	Emergency Power	USB Type-C Interface, DC 5V
	Power Supply	4 × AAA Alkaline Batteries
	Supported App	NGTeco Home
Door Compatibility	Door Type	Wooden Swing Door
	Door Thickness	30 to 60mm
	Opening Direction	All Direction (reversible lever design)
General	Product Dimensions (H×W×T)	154*61*28mm
	Operating Temperature	-20°C to 55°C (-4°F to 131°F)
	Operating Humidity	10% to 90% RH (Non-condensing)
	Certifications	CE
Package Contents	Exterior Assembly, Interior Assembly, Mortise Kit, IC Card * 2, Mechanical Key * 2, Studs & Screws Kit, Installation Template, Installation Guide, User Manual	

Mobile Application


Mobile Phone Unlocking




Member Management



Temporary Passcode



More Setting



Compatible With
NGTECO Home App







Download on the
App Store



GET IT ON
Google Play

Dimensions (mm)



NGTECO CO., LIMITED

www.ngtecto.com

service.ngtecto.com



Copyright © 2024 NGTECO CO., LOIMITED. All rights reserved.

V1.0 09/24/2024