Products V

Assemble kit

NVR More V

## **Tech specs**

# **NVR** (16-ch)

Network video recorder for 16 channels







## **Videostream**

## **NVR** models

#### 16-channel

With up to 4K resolution (25/30 FPS).

### IP cameras

- ONVIF (Profile S/T)
- RTSP

Learn more

## **Storage**

hard drive with a capacity of up to 16 TB (SATA connectivity, 3.5" size)

HDD not included. The hard drive with power consumption of up to 7 W can be connected.

Learn more

## **Decoding formats**

H.265

H.264

### Bandwidth

up to 100 Mbps

## Recommendations

The device operating voltage is  $110-240 \text{ V}\sim$ .

NVR is designed for indoor installation only.

### **Communication channels**

#### Ethernet

up to 100 Mbps

### Bluetooth

BLE frequency band: 2.400-2.4835 GHz

To set up an Ethernet connection.

## Radio signal power

2.5 mW (100 mW limit)

## **Key features**

## **Motion detection**

NVR has built-in software to detect the motion in the frame. Possible to switch between image analysis by NVR or camera algorithms.

## In-app video management system

- Videowall that combines images from all connected cameras.
- Event filters.
- Timeline with smooth preview.

## Visual verification of Ajax alarms

NVR allows setting up a scenario in which Ajax detectors trigger specific cameras to start recording. This results straight in mobile and desktop (monitoring) apps.

## Support for ONVIF authorization

Profile S

Profile T (partially)

Ajax cameras and NVRs can be integrated into third-party video management systems (VMS).

Learn more

### **Privacy**

Access rights distribution for users in mobile apps and for monitoring operators in PRO Desktop.

## **Power supply**

### Main

110-240 V~, 50/60 Hz, 0.6 A

Up to 24 W of mains power consumption.

## Backup

CR2032 battery, 3 V

Only to power the system clock.

## Sabotage protection

## Tamper alarm

Notifications about attempts to detach the device from the surface or remove it from the mounting panel.

Learn more

## **Enclosure**

### **Dimensions**

193 × 193 × 47 mm

## Weight

615 g

Without a hard drive.




## Operating temperature range

from 0 °C to +40 °C

## **Operating humidity**

up to 75%



47 mm

### **Protection class**

IP20

## Colors

Black



White



## Complete set

NVR

SmartBracket mounting panel

Power cable

Ethernet cable

Installation kit

Quick start guide

## Certification and compliance with standards



NVR (16-ch)



## **Additional information**

Compliance with standards

User manual

Learn more

Learn more

Warranty

24 months

Learn more

#### Subscribe

Subscribe to our emails about secure life. No spam.

#### Subscribe

#### Request extra help

- support@ajax.systems
- $@AjaxSystemsSupport\_Bot\\$
- Send a request



4,000,000

people worldwide under Ajax protection

Rating 4.7

#### Suggest a feature









#### **Products**

Intrusion protection

Video surveillance

Fire and life safety

Comfort and automation

All products

Services

System integrations

Ajax Ready products

Fibra wired protocol

Ajax radio protocols

#### Software

For users

Ajax PRO: Tool for Engineers

Ajax Desktop

Ajax PRO Desktop

Ajax Translator PRO

Ajax Cloud Signaling

Scenarios



Available on **App Store** 



Available on Google Play

#### Solutions

3/10/25, 6:58 p.m.

Customer stories

Solutions by facility type

Commercial fire detection and alarm system

Upgrades and retrofits

Why Ajax

How it works

NVR (16-ch) | Technical specifications

Manuals and articles

Compliance with standards

Tools

Ajax device compatibility

Video storage calculator

Video device calculator

Battery life calculator

Radio communication range calculator

Switches and outlets configurator

Fibra power supply calculator

All web tools

Connecting to CMS

Intrusion alarm monitoring

Video monitoring and visual alarm verification

Audio alarm verification

Company

Blog

About us

Press page

Events

Career

Ajax Next

Students at CES 2026

Reviews and feedback

For partners

For partners

Ajax Academy

Partner Portal

España Privacy policy Report a vulnerability GDPR White Paper NDAA Statement Cookie policy Anti-Spam Policy

End user agreement Warranty

© 2025 AJAX SYSTEMS CH. All rights reserved