

Flush Mount Desktop Power and Port Outlet

Rotating Opening, Two Power Outlets, Two USB-A Charging Ports, Two RJ45 Network Connections, One HDMI Connection, One VGA Connection, 1.5 m (5 ft.) Power Cord, Black

SKU: 164856 | EAN-13: 0766623164856 | UPC: 766623164856

Flush Mount Desktop Power and Port Outlet for concealable power, convenient display access and wired network connectivity

The Manhattan Flush Mount Desktop Power and Port Outlet is a low-profile charging and connectivity solution you can easily install into the receptacle cutout of an office desk, conference room table, workbench or other surface. Its rotatable panel lets you charge devices, connect displays and connect to the network when needed and otherwise keep the outlet closed for a clean, discreet look. When open, it offers two AC power outlets to connect notebooks, printers, monitors, projectors and more while two USB-A ports can charge mobile devices such as phones or tablets. The HDMI, VGA and Ethernet options offer much more convenient, extended display and network connections for floor-standing PCs than regular cables. The Flush Mount Desktop Power and Port Outlet makes it so you won't have to crawl under the desk to find a power strip or your cables again.

Features:

- Flush mount charging station with two power sockets and two USB-A charging ports
- Two USB-A charging ports with LED and output up to 2.1 A / 5 V DC (max.)
- HDMI passthrough connection with HDMI port and 1.5 m (5 ft.) HDMI cable - supports resolutions up to 1080p@60Hz
- VGA passthrough connection with VGA port and 1.5 m (5 ft.) VGA cable - supports resolutions up to 1080p@60Hz
- Gigabit Ethernet passthrough connection with two RJ45 ports and two 1.5 m (5 ft.) network cables
- Rotatable charging/connectivity panel that can be hidden when not in-use
- Ideal for installation into an office desk, conference room table, workbench or other surface
- Overload, overcurrent and overheating protection
- Built-in cable management for a clutter-free appearance
- Durable, high-quality aluminum alloy material
- Three-year warranty

Specifications:

Connections
• Two AC power outlets (NEMA 5-15)
• Two USB-A charging ports (2.1 A / 5 V DC max.)
• Two RJ45 Ethernet ports (10/100/1000 Mbps)
• One HDMI port (resolutions up to 1080p@60Hz)
• One VGA port (resolutions up to 1080p@60Hz)

Input Characteristics
• AC rated voltage: 110 - 125 V
• Frequency range: 50 - 60 Hz

Physical
• Housing dimensions (L x W x H): 311 x 110 x 103 mm (12.24 x 4.33 x 4.06 in.)
• Cutout dimensions for installation (L x W): 280 x 103 mm (11.02 x 4.06 in.)
• Power cable length: 1.5 m (5 ft.)
• HDMI cable length: 1.5 m (5 ft.)
• VGA cable length: 1.5 m (5 ft.)
• Network cable lengths: 1.5 m (5 ft.) each

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Net weight: 1.4 kg (3.09 lbs.)
• Gross weight: 1.8 kg (3.97 lbs.)

Operating Environment
• Operation temperature: 0 - 50°C (32 - 122°F)
• Storage temperature: -10 - 70°C (14 - 158°F)
• Humidity (noncondensing): 5 - 90% RH

Package Contents
• Flush Mount Desktop Power and Port Outlet
• Two mounting screws
• Instructions













For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.