

One-Port HDMI Wallplate

HDMI Female to HDMI Female, Coupler Type, White

SKU: 771719 | EAN-13: 0766623771719 | UPC: 766623771719

No mess, no fuss high-definition multimedia interface.

No more messy cables, no fussing with unsightly HDMI cables behind your TV, and no need to run long lengths of cable when connecting rooms. A Manhattan One-Port HDMI Wallplate screws easily into single-gang surface boxes, brackets and in-wall boxes. It requires no punching or installation other than connecting the HDMI cables (for in-wall installation CL2 cables or where other in-wall-rated cables are needed). Clean up your theater room or connect adjoining rooms easily. Enjoy full HD resolution up to 4K without the unsightly cables.

Features:

- HDMI coupler-type wallplate, HDMI female to HDMI female, one port
- Screw-in installation, for in-wall installation with CL2 or other in-wall-rated HDMI cables
- Compatible with single-gang surface mount boxes, brackets and in-wall mounted boxes
- Supports high-definition resolution; up to 4K
- Ideal for adding a professional, clutter-free finish to home theaters, home offices and other installations
- Gold-plated contacts
- Lifetime Warranty

Specifications:

Standards and Certifications
• HDMI
• ISO 9002
• RoHS2
• UL

General
• Single-gang mounting
• Supports 4K resolution
• Bandwidth: 18 Gbps, 340 MHz
• Connects two HDMI cables
• Intended for use with Manhattan HDMI Cables
• Coupler type, passive, connection
• Meets or exceeds existing HDMI standards

Connections
• Two HDMI female, 19-pin gold-plated

Physical
• 28-AWG cable gauge
• Cable Length: 10.5 cm (4 in.)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Faceplate Dimensions: 115 x 70 x 6 mm (4.5 x 2.76 x 0.2 in.)
• Housing: ABS plastic
• Weight: 54 g (1.9 oz.)
• Shielded
• Molded PVC

Electrical
• Current rating: 0.5 ADC
• Withstanding voltage: 300 VDC
• Insulation resistance: 10 MOhm
• Conductive resistance: 5 Ohm

Operating Environment
• Operation Temperature: 32 - 104°F (0 - 40°C)
• Storage Temperature: 14 - 140°F (-10 - 60°C)
• Humidity (noncondensing): 5 - 90%

Package Contents
• One-Port HDMI Wallplate
(Trim, one port insert, one HDMI coupler, two color-matching screws)



All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.





For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.