

4K 8-Port HDMI Splitter

4K@30Hz, AC Powered, Black

SKU: 207560 | EAN-13: 0766623207560 | UPC: 766623207560

Easily distribute a single Ultra-High-Definition (UHD) signal to multiple displays

The Manhattan 4K 8-Port HDMI Splitter with built-in booster streams a 4K HDMI signal from a single UHD source to up to eight UHD displays.

Best possible image quality and easy installation

Full compliance with HDMI and HDCP 1.4 ensures the Manhattan 4K 8-Port HDMI Splitter provides nothing short of high-quality performance and reliability. It delivers cinematic 4K resolution and supports 3D video and Deep Color as well as LPCM, DTS and Dolby TrueHD audio. Quickly connect HDMI cables (not included) and the power supply to complete this cost-effective 4 K solution — no software/hardware configuration or complicated settings required.

Features:

- Duplicates an Ultra-High-Definition (UHD) digital audio/video signal for up to eight UHD HDMI displays
- 4K@30Hz resolution, full 3D video and Deep Color
- Supports video amplifier bandwidth up to 340 MHz, 3.4 Gbps per channel (10.2 Gbps total) for 4Kx2K displays
- Supports 36-bit Deep Color (all channels) and xvYCC (x.v.Color)
- Supports compressed DTS-HD Master Audio, 7.1 surround sound, Dolby TrueHD and uncompressed LPCM 8 channel audio
- HDCP compliant
- Multiple splitters (three total) may be cascaded to support multiple displays
- Works with PlayStation and Xbox game systems, Blu-ray players, set-top boxes, satellite receivers and more
- Plug and play
- Three-year warranty

Specifications:

Standards and Certifications
• HDCP 1.4
• DVI 1.0
• CTS 1.4a
• CE
• FCC
• RoHS2

Connections
• One HDMI female input
• Eight HDMI female outputs
• One 5 VAC power female input

Signal Input/Output
• Input video signal: 0.5 – 1.0 V p-p
• Input DDC signal: 5 V p-p (TTL)
• Maximum single-link range: 10.2 Gbps and 4096x2160 at 24 Hz resolution
• Output video: HDMI 1.4, HDCP 1.4

Supported Video Resolutions
• DTV/HDTV: 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz

Physical
• LED indicators: power and port connection
• Dimensions (L x W x H): 210 x 66 x 27 mm (8.27 x 2.6 x 1.06 in.)
• Weight: 350 g (12.35 oz.)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Housing: metal

Operating Environment
• Operation Temperature: 0 – 40°C (32 – 104°F)
• Storage Temperature: -20 – 60°C (-4 – 140°F)
• Humidity (noncondensing): 0 – 96%

Package Contents
• 4K 8-Port HDMI Splitter
• Power adapter
• Quick Instruction Guide





All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.