

USB-A to USB-C Adapter

USB 3.2 Gen 2 Type-A Male to Type-C Female, 10 Gbps SuperSpeed+ USB, 3 A, Aluminum, Black

SKU: 153980 | EAN-13: 0766623153980 | UPC: 766623153980

Type-A to Type-C USB Adapter - easily convert a USB-A port to a USB-C port and bridge the gap from older to newer tech with ultra-fast 10G

The Manhattan USB-A to USB-C Adapter lets you connect standard USB-C accessories (e.g., USB hubs, external hard drives, sync/charging cables, etc.) to your USB-A-equipped computer, which is quite useful if you have an older model or your USB-C ports are already in use. Measuring only 37 mm (1.5 in.) in length, this passive adapter easily fits into a small pocket of your laptop bag for easy travel. With charge and sync capabilities up to 3 A and 10 Gbps respectively, you can quickly and easily keep your device ready for what's next.

Universal compatibility for easy installation

This universal USB 3.2 Gen 2 Type-A to Type-C adapter works with a wide range of computers because it requires no additional software or drivers. It also works with various operating systems such as Windows®, macOS®, Linux® and Chrome OS, so it’s multi-platform compatible.

Features:

- Easily connects a USB-C device to a USB-A port
- USB 3.2 Gen 2 compliant, supporting SuperSpeed+ transfer rates up to 10 Gbps; backward compatible with USB 3.0/USB 2.0/USB 1.1
- Ideal for connecting Type-C accessories like USB hubs, external hard drives, sync/charging cables and more
- Works with any compatible USB-A host device such as a PC, laptop, MacBook®, Chromebook™, Surface® and more
- Supports current up to 3 A
- Ultra-compact, portable and lightweight design for easy travel
- Durable aluminum housing
- Bus powered: no external power supply needed
- Plug-and-play installation; Windows®, macOS®, Linux® and Chrome OS™ compatible
- Supports hot swapping
- Supports only USB data transfer and charging - does not support audio/video signal transmission
- Lifetime warranty

Specifications:

Standards and Certifications
• USB 3.2 Gen 2
• CE
• RoHS
• REACH
• UKCA

Connections
• One USB-C 24-pin, female
• One USB-A 9-pin, male
• Nickel-plated contacts

Electrical
• Withstanding voltage: 300.0 V DC 10 ms

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Insulation resistance: 5 MOhm
• Contact resistance: 2 Ohm
• Supported current: 3.0 A

Physical
• Dimensions (L x W x H): 37 x 15 x 7 mm (1.46 x 0.59 x 0.39 in.)
• Net weight: 5 g (0.18 oz.)
• Gross weight: 10 g (0.35 oz.)
• Aluminum housing

Operating Environment
• Operation temperature: 0 - 85°C (32 - 185°F)
• Storage temperature: -10 - 85°C (14 - 185°F)
• Humidity (non-condensing): 10 - 90% RH

System Requirements
• Windows 7/8.1/10/11, Linux, Chrome OS or macOS
• NOTE: Supports only USB data transfer and charging - does not support audio/video signal transmission

Package Contents
• USB-A to USB-C Adapter









For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.





For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.